

SolVin 372NA Polyvinyl Chloride Low Viscosity Paste

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Powder

Material Notes:

Made by emulsion polymerization for plastisol preparation. MAIN APPLICATIONS Spread coating : - flooring foam layer - flooring impregnation layer - flooring backing foam - tarpaulins - coil coating. Molding and dipping. ADVANTAGES - High filler acceptance. - Not sticking over a wide temperature range on a pregelation drum. Information provided by SolVin.

Order this product through the following link:

http://www.lookpolymers.com/polymer_SolVin-372NA-Polyvinyl-Chloride-Low-Viscosity-Paste.php

Physical Properties	Metric	English	Comments
Volatile Organic Compounds (VOC) Content	<= 0.30 g/l	<= 0.30 g/l	ISO 1269
Particle Size	125 Åµm	125 Åµm	<0.2 g/kg greater than value; ISO 787-18
Viscosity Measurement	72	72	K value; ISO 1628-2

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China