

SolVin 460SL Polyvinyl Chloride grafted copolymer

Category : Polymer , Thermoplastic , Vinyl (PVC)

Material Notes:

Made by suspension polymerization. Special product for calendered film from the high temperature process. APPLICATIONS Calendering : unplasticized PVC - film : high temperature process Extrusion : unplasticized PVC - sheet, film Information provided by SolVin.

Order this product through the following link:

http://www.lookpolymers.com/polymer_SolVin-460SL-Polyvinyl-Chloride-grafted-copolymer.php

Physical Properties	Metric	English	Comments
Volatile Organic Compounds (VOC) Content	<= 0.30 g/l	<= 0.30 g/l	ISO 1269
Apparent Bulk Density	0.590 g/cc	0.0213 lb/in ³	ISO 60
Particle Size	63 µm	63 µm	>90% greater than value; ISO 1624
	250 µm	250 µm	<2% greater than value; ISO 1624
Viscosity Test	87 cm ³ /g	87 cm ³ /g	Reduced viscosity, K value = 59.5; ISO 1628-2

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China