

SolVin 560RA Copolymer of Vinyl Chloride and Vinyl Acetate

Category : Polymer , Thermoplastic , Vinyl (PVC) , Polyvinyl Chloride - Polyvinyl Acetate Copolymer

Material Notes:

Made by suspension polymerization. APPLICATIONS Extrusion : sheets for vacuum-forming, for deformations of over 500 % Calendering :

rigid sheets for deep thermoformingInformation provided by SolVin.

Order this product through the following link:

http://www.lookpolymers.com/polymer_SolVin-560RA-Copolymer-of-Vinyl-Chloride-and-Vinyl-Acetate.php

Physical Properties	Metric	English	Comments
Volatile Organic Compounds (VOC) Content	<= 0.30 g/l	<= 0.30 g/l	ISO 1269
Apparent Bulk Density	0.520 g/cc	0.0188 lb/in³	ISO 60
Particle Size	63 µm	63 µm	>60% greater than value; ISO 1624
Viscosity Test	89 cm³/g	89 cm³/g	Reduced viscosity, K value = 60; ISO 1628-2
Vinyl Acetate Content	8.0 %	8.0 %	Solvay Test

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com Email : sales@lookpolymers.com Tel : +86 021-51131842 Mobile : +86 13061808058 Skype : lookpolymers Address : United North Road 215,Fengxian District, Shanghai City,China