

SolVin 561SF Vinyl Chloride - Vinyl Acetate copolymer Paste - filler

Category: Polymer, Thermoplastic, Vinyl (PVC), Polyvinyl Chloride - Polyvinyl Acetate Copolymer

Material Notes:

Made by suspension polymerization. APPLICATIONS This resin has been especially developed for automotive mastics. Information provided by SolVin.

Order this product through the following link:

http://www.lookpolymers.com/polymer_SolVin-561SF-Vinyl-Chloride-Vinyl-Acetate-copolymer-Paste-filler.php

Physical Properties	Metric	English	Comments
Volatile Organic Compounds (VOC) Content	<= 0.30 g/l	<= 0.30 g/l	ISO 1269
Apparent Bulk Density	>= 0.750 g/cc	>= 0.0271 lb/in³	Compacted; ISO 60
Particle Size	<= 35 Âμm	<= 35 Âμm	average; ISO 1624
	90 µm	90 Âμm	<1 g/kg greater than value; ISO 1624
Viscosity Test	92 cm³/g	92 cm³/g	Reduced viscosity, K value = 61; ISO 1628-2
Vinyl Acetate Content	>= 6.0 %	>= 6.0 %	Solvay Test

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China