

Solvay Chemicals KaCeFlux Potassium Fluoroaluminate

Category : Ceramic

Material Notes:

Standard flux for brazing aluminum.HS No.: 3810100000 /CAS-No.: 60304-36-1 and 14484-69-6Uses: Automotive Sector, Commercial & Residential Air Conditioning, Refrigeration and Household & Electrical AppliancesInformation provided by Solvay

Order this product through the following link:

http://www.lookpolymers.com/polymer_Solvay-Chemicals-KaCeFlux-Potassium-Fluoroaluminate.php

Physical Properties	Metric	English	Comments
Bulk Density	0.300 - 0.600 g/cc	0.0108 - 0.0217 lb/in ³	
Density	2.80 g/cc @Temperature 20.0 Â°C	0.101 lb/in ³ @Temperature 68.0 Â°F	
Solubility in Water	0.45 %	0.45 %	

Thermal Properties	Metric	English	Comments
Melting Point	560 - 575 Â°C	1040 - 1070 Â°F	

Descriptive Properties	Value	Comments
Appearance	White powder	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China