

Solvay Chemicals NOCOLOK® Braze Paste x43-7

Category: Fluid

Material Notes:

A braze paste specifically formulated for providing viscous mixture of flux and alloy for brazing noncladded aluminum materials, including 1100, 3001 and 6061 series aluminum. Uses: Automotive Sector, Commercial & Residential Air Conditioning, Refrigeration and Household & Electrical AppliancesInformation provided by Solvay

Order this product through the following link:

http://www.lookpolymers.com/polymer_Solvay-Chemicals-NOCOLOK-Braze-Paste-x43-7.php

Mechanical Properties	Metric	English	Comments
Tensile Strength	24.1 MPa	3500 psi	

Thermal Properties	Metric	English	Comments
Melting Point	577 - 613 °C	1070 - 1140 °F	
Solidus	577 °C	1070 °F	
Liquidus	613 °C	1140 °F	

Component Elements Properties	Metric	English	Comments
Aluminum, Al	92.25 - 93.5 %	92.25 - 93.5 %	
Silicon, Si	6.5 - 7.5 %	6.5 - 7.5 %	

Descriptive Properties	Value	Comments
Appearance	silver grey	
Composition	>0.15%	Others Total

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China