

## Solvay Chemicals NOCOLOK® Braze Paste x45-10

Category : Fluid

**Material Notes:**

NOCOLOK® Braze Paste X45-10 is specifically formulated for providing viscous mixture or flux and alloy for brazing noncladded aluminum materials. Uses: Automotive Sector, Commercial & Residential Air Conditioning, Refrigeration and Household & Electrical Appliances  
Information provided by Solvay

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Solvay-Chemicals-NOCOLOK-Braze-Paste-x45-10.php](http://www.lookpolymers.com/polymer_Solvay-Chemicals-NOCOLOK-Braze-Paste-x45-10.php)

Mechanical Properties	Metric	English	Comments
Tensile Strength	24.1 MPa	3500 psi	
Taber Abrasion, mg/1000 Cycles	15	15	CS<sub>17</sub> grind wheel; 1kg load; ASTM D4060

Thermal Properties	Metric	English	Comments
Melting Point	577 - 590 Å°C	1070 - 1090 Å°F	
Solidus	577 Å°C	1070 Å°F	
Liquidus	590 Å°C	1090 Å°F	

Component Elements Properties	Metric	English	Comments
Aluminum, Al	89.35 - 90.5 %	89.35 - 90.5 %	
Silicon, Si	9.5 - 10 %	9.5 - 10 %	

Descriptive Properties	Value	Comments
Appearance	silver grey	
Composition	>0.15%	Others Total

### Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China