

Solvay Chemicals NOCOLOK® Braze Paste x47-12

Category : Fluid

Material Notes:

A braze paste specifically formulated for providing viscous mixture of flux and alloy for brazing noncladded aluminum materials. Paste can be dispensed manually by brush, syringe, or with automatic dispensing equipment. Uses: Automotive Sector, Commercial & Residential Air Conditioning, Refrigeration and Household & Electrical Appliances Information provided by Solvay

Order this product through the following link:

http://www.lookpolymers.com/polymer_Solvay-Chemicals-NOCOLOK-Braze-Paste-x47-12.php

Mechanical Properties	Metric	English	Comments
Tensile Strength	24.1 MPa	3500 psi	

Thermal Properties	Metric	English	Comments
Melting Point	577 - 582 Â°C	1070 - 1080 Â°F	
Solidus	577 Â°C	1070 Â°F	
Liquidus	582 Â°C	1080 Â°F	

Component Elements Properties	Metric	English	Comments
Aluminum, Al	86.85 - 89 %	86.85 - 89 %	
Silicon, Si	11 - 13 %	11 - 13 %	

Descriptive Properties	Value	Comments
Appearance	silver grey	
Composition	>0.15%	Others Total

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China