

## Solvay Chemicals NOCOLOK® CB Flux Potassium Silicofluoride

Category : Ceramic

**Material Notes:**

Reactive flux for brazing of aluminum CAS-No.: 16871-90-2 Uses: Automotive Sector, Commercial & Residential Air Conditioning, Refrigeration and Household & Electrical Appliances Information provided by Solvay

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Solvay-Chemicals-NOCOLOK-CB-Flux-Potassium-Silicofluoride.php](http://www.lookpolymers.com/polymer_Solvay-Chemicals-NOCOLOK-CB-Flux-Potassium-Silicofluoride.php)

Physical Properties	Metric	English	Comments
Bulk Density	0.500 - 0.900 g/cc	0.0181 - 0.0325 lb/in <sup>3</sup>	
Density	2.67 g/cc @Temperature 17.0 °C	0.0965 lb/in <sup>3</sup> @Temperature 62.6 °F	
Solubility in Water	0.177 %	0.177 %	
Molecular Weight	220.3 g/mol	220.3 g/mol	

Thermal Properties	Metric	English	Comments
Melting Point	565 - 572 °C	1050 - 1060 °F	in contact with aluminium
	>= 820 °C	>= 1510 °F	

Descriptive Properties	Value	Comments
Appearance	White powder	

### Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China