

Solvay Chemicals NOCOLOK® Flux Drystatic Potassium Fluoroaluminate

Category : Ceramic

Material Notes:

Flux using electrostatic/dry powder coating. Classifications: HS No.: 38109090 /CAS-No.: 60304-36-1Uses: Automotive Sector, Commercial & Residential Air Conditioning, Refrigeration and Household & Electrical AppliancesInformation provided by Solvay

Order this product through the following link:

http://www.lookpolymers.com/polymer_Solvay-Chemicals-NOCOLOK-Flux-Drystatic-Potassium-Fluoroaluminate.php

Physical Properties	Metric	English	Comments
Bulk Density	0.600 - 0.900 g/cc	0.0217 - 0.0325 lb/in ³	
Density	2.80 g/cc @Temperature 20.0 Â°C	0.101 lb/in ³ @Temperature 68.0 Â°F	
Solubility in Water	0.45 %	0.45 %	

Thermal Properties	Metric	English	Comments
Melting Point	565 - 572 Â°C	1050 - 1060 Â°F	

Descriptive Properties	Value	Comments
Appearance	white powder	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China