

Solvay Chemicals NOCOLOK® Li Flux Drystatic

Category : Ceramic

Material Notes:

Flux for aluminum brazing with further reduced residue solubility and improved corrosion characteristics and using electrostatic/dry powder coating. HS No.: 38109090 /CAS-No.: 60304-36-1 and 13821-20-0 Uses: Automotive Sector, Commercial & Residential Air Conditioning, Refrigeration and Household & Electrical Appliances Information provided by Solvay

Order this product through the following link:

http://www.lookpolymers.com/polymer_Solvay-Chemicals-NOCOLOK-Li-Flux-Drystatic.php

Physical Properties	Metric	English	Comments
Bulk Density	0.600 - 0.900 g/cc	0.0217 - 0.0325 lb/in ³	
Density	2.80 - 3.00 g/cc @Temperature 20.0 Â°C	0.101 - 0.108 lb/in ³ @Temperature 68.0 Â°F	
Solubility in Water	0.45 %	0.45 %	

Thermal Properties	Metric	English	Comments
Melting Point	569 - 577 Â°C	1060 - 1070 Â°F	

Descriptive Properties	Value	Comments
Appearance	White powder	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China