

Solvay Chemicals NOCOLOK® Precoating (water soluble)

Category : Fluid

Material Notes:

NOCOLOK® Precoating can be used in mixture with NOCOLOK® Flux or NOCOLOK® Zn Flux and water to improve adhesion of the flux coating. Uses: Automotive Sector, Commercial & Residential Air Conditioning, Refrigeration and Household & Electrical

Appliances Information provided by Solvay

Order this product through the following link:

http://www.lookpolymers.com/polymer_Solvay-Chemicals-NOCOLOK-Precoating-water-soluble.php

Physical Properties	Metric	English	Comments
Density	1.00 g/cc	0.0361 lb/in ³	
Viscosity	>= 40 cP	>= 40 cP	
Vapor Pressure	0.0220 bar	16.5 torr	bibliographical ref.

Thermal Properties	Metric	English	Comments
Boiling Point	100 °C	212 °F	bibliographical ref.

Descriptive Properties	Value	Comments
Appearance	Viscous liquid	
Color	milky	
Explosion limit	0.013	Lower
	0.095	Higher

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China