

Solvay Chemicals NOCOLOKÂ® Thickener (water soluble)

Category : Fluid

Material Notes:

NOCOLOKÂ® Thickener can be used in mixture with NOCOLOKÂ® Binder, water and NOCOLOKÂ® Flux to improve adhesion of the flux coating. CAS-No.: 111-76-2Uses: Automotive Sector, Commercial & Residential Air Conditioning, Refrigeration and Household & Electrical AppliancesInformation provided by Solvay

Order this product through the following link:

http://www.lookpolymers.com/polymer_Solvay-Chemicals-NOCOLOK-Thickener-water-soluble.php

Physical Properties	Metric	English	Comments
Density	0.980 g/cc	0.0354 lb/inÂ³	
Solids Content	13 - 17 %	13 - 17 %	
Vapor Pressure	0.100 bar	75.0 torr	bibliographical ref.

Thermal Properties	Metric	English	Comments
Boiling Point	100 Â°C	212 Â°F	bibliographical ref.

Descriptive Properties	Value	Comments
Composition	38-42%	Solvent organic
Explosion limit	0.011	Lower
	0.106	Higher
Solid volume	16 l/100 kg	
Viscosity	15 s 4 mm	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China