

Solvay Chemicals NOCOLOK® Ultra Flux Paste

Category : Fluid

Material Notes:

A flux paste specifically formulated for providing a viscous homogeneous mixture of NOCOLOK® Flux (35-50%) in an organic carrier for brazing aluminum clad interfaces where traditional water based fluxing is not suitable. Uses: Automotive Sector, Commercial & Residential Air Conditioning, Refrigeration and Household & Electrical Appliances. Information provided by Solvay

Order this product through the following link:

http://www.lookpolymers.com/polymer_Solvay-Chemicals-NOCOLOK-Ultra-Flux-Paste.php

Physical Properties	Metric	English	Comments
Density	1.20 - 1.40 g/cc	0.0434 - 0.0506 lb/in ³	

Thermal Properties	Metric	English	Comments
Melting Point	565 - 572 °C	1050 - 1060 °F	(Addition of CsAlF ₄ will reduce melting point)

Descriptive Properties	Value	Comments
Appearance	white	
Composition	35-50%	NOCOLOK®
	Balance	Carrier

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China