

## Solvay Specialty Polymers Halar® 6914 Ethylene Chlorotrifluoroethylene Copolymer (ECTFE)

Category: Polymer, Thermoplastic, Fluoropolymer, ETFE/ECTFE, ECTFE Fluoropolymer

## **Material Notes:**

Halar® 6914 is a gray, semi-crystalline melt processable fluorinated primer. It is designed to be applied directly to substrates by electrostatic or fluidized bed techniques. In particular Halar® 6914 is recommended for use as a primer on aluminum large surface area parts in protection and anti-corrosion applications. Features: Bondability; Good Adhesion; Good Chemical Resistance; Good Color Stability; Good Corrosion Resistance; Good Thermal Stability; Semi CrystallineUses: Bonding; Coating ApplicationsAdditional Properties: Average Particle Size - ASTM D1921 80 µmInformation provided by Solvay Specialty Polymers.

## Order this product through the following link:

http://www.lookpolymers.com/polymer\_Solvay-Specialty-Polymers-Halar-6914-Ethylene-Chlorotrifluoroethylene-Copolymer-ECTFE.php

Physical Properties	Metric	English	Comments
Density	1.68 g/cc	0.0607 lb/in³	ASTM D1505
Melt Flow	7.0 g/10 min	7.0 g/10 min	ASTM D1238
	@Load 2.16 kg, Temperature 275 °C	@Load 4.76 lb, Temperature 527 °F	

Thermal Properties	Metric	English	Comments
Melting Point	225 °C	437 °F	DSC

Descriptive Properties	Value	Comments
Availability	Africa & Middle East	
	Asia Pacific	
	Europe	
	Latin America	
	North America	
Color	Grey	
Form	Powder ique Coating	
Processing Technique		

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com



Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China