

## Solvay Specialty Polymers Polymist® XPP 552 Polytetrafluoroethylene (PTFE)

Category: Polymer, Thermoplastic, Fluoropolymer, PTFE, PTFE Powder

## **Material Notes:**

Polymist $\hat{A}$ ® XPP 552 is a white PTFE micronized powder composed of discrete particles. Designed for use in critical engineering and high end performance Coatings and Inks, Polymist $\hat{A}$ ® XPP 552 will improve non-stick properties, mar and abrasion resistance as well as slip and rub resistance. Uses: AdditiveAdditional Properties: Average Particle Size - Internal Method 3.3  $\hat{A}$ µm; Average Particle Size - Internal Method 8.0  $\hat{A}$ µm; Bulk Density - ASTM D4895 > 325 g/l; Grind in Oil - NPIRI 1.50; Melt Temperature - ASTM D3418 320 to 330  $\hat{A}$ °C; Specific Surface Area - Internal Method 3.0  $\hat{m}\hat{A}$ 2/glnformation provided by Solvay Specialty Polymers.

## Order this product through the following link:

http://www.lookpolymers.com/polymer\_Solvay-Specialty-Polymers-Polymist-XPP-552-Polytetrafluoroethylene-PTFE.php

Descriptive Properties	Value	Comments
Availability	Asia Pacific	
	Europe	
	North America	
Color	White	
Form	Powder	

## Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China