

Solvay TECHNYL® 2210HS PA66, Conditioned

Category : Polymer , Thermoplastic , Nylon , Nylon 66

Material Notes:

Description: Polyamide 66, unfilled, long-term stabilized, lubricated for injection molding. Available in: Asia Pacific Product Applications: TECHNYL® 2210HS is used in all sectors of industry, offering an excellent long-term heat stability & productivity. This grade is used for: Connector, Pin of automobile, Power steering reservoir tank, Switch, Canister, Fuel filler tube. This product is available in Black color. Information provided by Rhodia, Rhodia has been acquired by Solvay.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Solvay-TECHNYL-2210HS-PA66-Conditioned.php

Physical Properties	Metric	English	Comments
Density	1.54 g/cc	0.0556 lb/in ³	ASTM D792

Processing Properties	Metric	English	Comments
Moisture Content	<= 0.20 %	<= 0.20 %	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China