

Spartech Royalite R59 ABS/PVC Fire Rated Sheet

Category : Polymer , Thermoplastic , ABS Polymer , ABS/PVC Alloy , Vinyl (PVC)

Material Notes:

Description: Fire Rated Sheet Information provided by Spartech.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Spartech-Royalite-R59-ABSPVC-Fire-Rated-Sheet.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.18 - 1.25 g/cc	1.18 - 1.25 g/cc	ASTM D792

Mechanical Properties	Metric	English	Comments
Hardness, Rockwell R	96	96	ASTM D785
Tensile Strength, Yield	35.9 MPa	5200 psi	ASTM D638
Flexural Yield Strength	55.2 MPa	8000 psi	ASTM D790
Flexural Modulus	2.00 GPa	290 ksi	ASTM D790
Izod Impact, Notched	5.34 J/cm	10.0 ft-lb/in	73°F; ASTM D256
	1.07 J/cm	2.00 ft-lb/in	ASTM D256
	@Temperature -28.9 °C	@Temperature -20.0 °F	
Impact Test	40.7 J	30.0 ft-lb	Dynatup Instrumented Impact; ASTM D3763
	@Temperature 22.8 °C	@Temperature 73.0 °F	

Thermal Properties	Metric	English	Comments
CTE, linear	82.8 - 99.0 $\mu\text{m}/\text{m}\cdot\text{°C}$	46.0 - 55.0 $\mu\text{in}/\text{in}\cdot\text{°F}$	ASTM D696
	@Temperature 20.0 °C	@Temperature 68.0 °F	
Deflection Temperature at 0.46 MPa (66 psi)	87.8 °C	190 °F	ASTM D648
Deflection Temperature at 1.8 MPa (264 psi)	76.7 °C	170 °F	ASTM D648
Flammability, UL94	V-0	V-0	5V

Descriptive Properties	Value	Comments
Flammability	Passes	MVSS (Motor Vehicle Safety Standard) 302

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China