

Struktol POLYDIS 3622 Elastomer modified epoxy prepolymer

Category : Other Engineering Material , Additive/Filler for Polymer , Polymer , Thermoset , Epoxy

Material Notes:

Applications: STRUKTOL VP 3622 is used where conventional epoxy systems and prepolymers are unable to satisfy the demands of for example impact, flexural and peel strength. Information provided by Struktol

Order this product through the following link:

http://www.lookpolymers.com/polymer_Struktol-POLYDIS-3622-Elastomer-modified-epoxy-prepolymer.php

Physical Properties	Metric	English	Comments
Density	1.12 g/cc	0.0405 lb/in ³	
Viscosity	9500 cP @Temperature 25.0 Â°C	9500 cP @Temperature 77.0 Â°F	Dynamic

Chemical Properties	Metric	English	Comments
Acid Value	<= 1.0	<= 1.0	

Processing Properties	Metric	English	Comments
Shelf Life	>= 12.0 Month	>= 12.0 Month	in original sealed containers at temperatures less than 40Â°C

Descriptive Properties	Value	Comments
Appearance	Clear, slightly yellowish, liquid epoxy resin	
Elastomer Content %	40 Polyether	
Epoxy Equivalent Weight (g/Eq)	330	
Resin-base of the prepolymer	DGEBA	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China