

Struktol TPW 613 Processing Additive

Category : Other Engineering Material , Additive/Filler for Polymer , Polymer

Material Notes:

STRUKTOLÂ® TPW 613 is a functional lubricant package designed to provide superior filler wetting and dispersion characteristics in a wide range of polymer systems. This product has been engineered to provide significant processing improvements and output rate increases for filled compounds. Applications: STRUKTOLÂ® TPW 613 is recommended for wood-filled polyolefins where improved filler dispersion and surface quality is required. Information provided by Struktol

Order this product through the following link:

http://www.lookpolymers.com/polymer_Struktol-TPW-613-Processing-Additive.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.005 g/cc	1.005 g/cc	
Additive Loading	1.0 - 7.0 %	1.0 - 7.0 %	

Thermal Properties	Metric	English	Comments
Dropping Point	65.0 - 78.0 Â°C	149 - 172 Â°F	

Processing Properties	Metric	English	Comments
Shelf Life	>= 24.0 Month	>= 24.0 Month	

Descriptive Properties	Value	Comments
Appearance	Pastille or beads	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China