

Struktol V-DSP Processing Additive

Category: Other Engineering Material, Additive/Filler for Polymer, Polymer

Material Notes:

Fatty acid esterTypical Applications: STRUKTOL® V-DSP is a highly compatible, internal PVC lubricant. It is particularly good at improving melt flow thus reducing amperage and head pressure for complicated profiles. STRUKTOL® V-DSP is also very effective at improving melt flow in injecting molding applications. It is particularly good for clear applications. Features: STRUKTOL® V-DSP is very effective at reducing viscosity in injection molding and profile extrusion. STRUKTOL® V-DSP also yields exceptional clarity in clear injection molding, blow molding, and extrusion applications.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Struktol-V-DSP-Processing-Additive.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.997 g/cc	0.997 g/cc	
Additive Loading	0.70 - 1.2 %	0.70 - 1.2 %	phr

Thermal Properties	Metric	English	Comments
Melting Point	47.0 - 57.0 °C	117 - 135 °F	

Processing Properties	Metric	English	Comments
Shelf Life	>= 24.0 Month	>= 24.0 Month	

Descriptive Properties	Value	Comments
Appearance	White to off-white pastille	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China