

Struktol V-HCS Co-Stabilizing Processing Additive

Category : Other Engineering Material , Additive/Filler for Polymer , Polymer

Material Notes:

Blend fatty acid derived and functional inorganic materials. Applications: STRUKTOL® V-HCS is recommended for us with recycled rigid PVC where additional stabilization and lubrication is needed to reduce yellowing, burning and sticking in extrusion, injection molding and calendaring. It is especially useful in allowing higher loadings of PVC regrind (post industrial or post consumer) in virgin formulations. It also allows for longer production runs between shutdowns due to degradation. Information provided by Struktol

Order this product through the following link:

http://www.lookpolymers.com/polymer_Struktol-V-HCS-Co-Stabilizing-Processing-Additive.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.46 g/cc	1.46 g/cc	
Additive Loading	0.50 - 2.0 %	0.50 - 2.0 %	

Thermal Properties	Metric	English	Comments
Melting Point	>= 100 Â°C	>= 212 Â°F	

Processing Properties	Metric	English	Comments
Shelf Life	>= 24.0 Month	>= 24.0 Month	

Descriptive Properties	Value	Comments
Appearance	White powder	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China