

Struktol V-HRW LUBRICANT ADDITIVE FOR PVC AND POLYMER PROCESSING

Category : Other Engineering Material , Additive/Filler for Polymer , Polymer

Material Notes:

Applications: STRUKTOL® V-HRW is a highly compatible, rigid PVC lubricant with both internal and external properties. It is particularly useful in clear PVC articles due to its excellent clarity and low water blush. It can be used in blow molding, injection molding, extrusion and is especially effective in calendaring applications and in products that will be printed, bonded or laminated. Information provided by Struktol Sanctioned for use by the Food and Drug Administration in a number of applications, listed in the following sections of Title 21 of the Code of Federal Regulations: 176.170176.210177.1200177.121177.2420178.3280

Order this product through the following link:

http://www.lookpolymers.com/polymer_Struktol-V-HRW-LUBRICANT-ADDITIVE-FOR-PVC-AND-POLYMER-PROCESSING.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.023 g/cc	1.023 g/cc	

Thermal Properties	Metric	English	Comments
Dropping Point	>= 85.0 °C	>= 185 °F	

Processing Properties	Metric	English	Comments
Shelf Life	>= 24.0 Month	>= 24.0 Month	

Descriptive Properties	Value	Comments
Appearance	White to off white flakes or powder	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China