

Struktol V-SSE Processing Additive

Category : Other Engineering Material , Additive/Filler for Polymer , Polymer

Material Notes:

Fatty acid ester Typical Applications: STRUKTOLÂ® V-SSE has both internal and external lubricant characteristics. It is used in calendering, extrusion and injection molding applications. It also has excellent applicability in extruded complex profile. Features: STRUKTOLÂ® V-SSE is noted for superior weathering characteristics. STRUKTOL V-SSE is also noted for its ability to reduce melt viscosity in both injection molding and extrusion. STRUKTOLÂ® V-SSE is particularly resistant to plate out and is noted for its ability to improve printability of extruded parts (particularly when substituting for paraffin). FDA Status: 178.391

Order this product through the following link:

http://www.lookpolymers.com/polymer_Struktol-V-SSE-Processing-Additive.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.935 g/cc	0.935 g/cc	
Additive Loading	0.70 - 1.0 %	0.70 - 1.0 %	phr

Thermal Properties	Metric	English	Comments
Melting Point	54.0 - 61.0 Â°C	129 - 142 Â°F	

Processing Properties	Metric	English	Comments
Shelf Life	>= 24.0 Month	>= 24.0 Month	

Descriptive Properties	Value	Comments
Appearance	Off-white to beige pastilles or beads	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China