

Styrolution Novodur® 532 ABS

Category : Polymer , Thermoplastic , ABS Polymer , Acrylonitrile Butadiene Styrene (ABS), Sheet

Material Notes:

Novodur 532 is an extrusion grade optimized for sheet applications. It has high impact properties and good processability. Information provided by Styrolution

Order this product through the following link:

http://www.lookpolymers.com/polymer_Styrolution-Novodur-532-ABS.php

Physical Properties	Metric	English	Comments
Melt Flow	2.5 g/10 min @Load 10.0 kg, Temperature 220 °C	2.5 g/10 min @Load 22.0 lb, Temperature 428 °F	ISO 1133

Mechanical Properties	Metric	English	Comments
Tensile Strength, Yield	38.0 MPa	5510 psi	ISO 527

Thermal Properties	Metric	English	Comments
Vicat Softening Point	95.0 °C @Load 5.10 kg	203 °F @Load 11.2 lb	120°C/h; ASTM D 1525

Optical Properties	Metric	English	Comments
Gloss	90 %	90 %	Specular Gloss, 60°; ASTM D 523

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China