

Styrolution Novodur® 650 ABS

Category : Polymer , Thermoplastic , ABS Polymer , Acrylonitrile Butadiene Styrene (ABS), Impact Grade, Molded

Material Notes:

Novodur 650 is an injection molding grade of ABS with high impact strength, high flow and high gloss. Information provided by Styrolution

Order this product through the following link:

http://www.lookpolymers.com/polymer_Styrolution-Novodur-650-ABS.php

Physical Properties	Metric	English	Comments
Melt Flow	22 g/10 min @Load 10.0 kg, Temperature 220 °C	22 g/10 min @Load 22.0 lb, Temperature 428 °F	ISO 1133

Mechanical Properties	Metric	English	Comments
Tensile Strength, Yield	44.0 MPa	6380 psi	ISO 527

Thermal Properties	Metric	English	Comments
Vicat Softening Point	98.0 °C @Load 5.10 kg	208 °F @Load 11.2 lb	120°C/h; ASTM D 1525

Optical Properties	Metric	English	Comments
Gloss	87 %	87 %	Specular Gloss, 60°; ASTM D 523

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China