

## Styrolution Novodur® 970 ABS

Category : Polymer , Thermoplastic , ABS Polymer , Acrylonitrile Butadiene Styrene (ABS), Impact Grade, Molded

**Material Notes:**

Novodur 970 is an injection molding grade of ABS with high impact strength and good paintability. Information provided by Styrolution

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Styrolution-Novodur-970-ABS.php](http://www.lookpolymers.com/polymer_Styrolution-Novodur-970-ABS.php)

Physical Properties	Metric	English	Comments
Melt Flow	22 g/10 min @Load 10.0 kg, Temperature 220 °C	22 g/10 min @Load 22.0 lb, Temperature 428 °F	ISO 1133

Mechanical Properties	Metric	English	Comments
Tensile Strength, Yield	41.0 MPa	5950 psi	ISO 527

Thermal Properties	Metric	English	Comments
Vicat Softening Point	98.0 °C @Load 5.10 kg	208 °F @Load 11.2 lb	120°C/h; ASTM D 1525

Optical Properties	Metric	English	Comments
Gloss	89 %	89 %	Specular Gloss, 60°; ASTM D 523

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China