

## Styron SE PB-5800 Schkopau Low-cis Polybutadiene Rubber (PBR)

Category: Polymer, Thermoset, Rubber or Thermoset Elastomer (TSE)

## **Material Notes:**

Composition: SE PB-5800 - Schkopau is a low-cis polybutadiene synthetic rubber. It is produced by anionic solution polymerization adjusted for a high level of linearity. SE PB-5800 â€" Schkopau is translucent to white in appearance and contains a non-staining stabilizer which complies with compositional requirements of the food packaging regulations of European countries and the USA (Styron may be consulted regarding applicable regulations). Application: SE PB-5800 is used to manufacture High-Impact Polystyrene or ABS, supporting grafting processes with its content of reactive vinyl-groups. Information provided by Styron

## Order this product through the following link:

http://www.lookpolymers.com/polymer\_Styron-SE-PB-5800-Schkopau-Low-cis-Polybutadiene-Rubber-PBR.php

Physical Properties	Metric	English	Comments
	0.30 %	0.30 %	
Volatiles	@Treatment Temp. 105 °C, Time 3600 sec	@Treatment Temp. 221 °F, Time 1.00 hour	5 g in hot air oven; ASTM D5668
Viscosity	175 cP	175 cP	5% max in styrene solution at 25°C; ASTM D455
Mooney Viscosity	51	51	[MU] ML 1+4; ASTM D1646
	@Temperature 100 °C	@Temperature 212 °F	
Ash	0.050 %	0.050 %	ASTM D5667

Descriptive Properties	Value	Comments
Color	5 АРНА	
Composition	0.12	Vinyl content, FTIR
	0.37	Cis-1,4 content, FTIR
Gel rating	1-2	

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China