

Suzhou Hipro Polymers Hiprolon® 211 PES Colorized Nylon powder

Category: Polymer, Renewable/Recycled Polymer, Thermoplastic, Nylon

Material Notes:

Hiprolon® 211 PES colorized electrostatic polyamide powder is fully comprised of bio-renewable raw materials. It has excellent weather ability, chemical resistance, wear resistance, impact resistance, and superior adhesion strength with metal surfaces. It is widely used for coating of auto parts, hard wares, water pipes racks et al. Available in various colors to provide a customized product. It can be applied to subjects with a 0.7mm-0.3mm thickness range, and it can also achieve a thinner thickness when it is not coated by dipping. The optimal coating thickness is 0.12-0.15mm.Information provided by Suzhou Hipro Polymers Co. Ltd

Order this product through the following link:

http://www.lookpolymers.com/polymer_Suzhou-Hipro-Polymers-Hiprolon-211-PES-Colorized-Nylon-powder.php

Physical Properties	Metric	English	Comments
Density	1.10 g/cc	0.0397 lb/in³	ISO 1183
Water Absorption	0.90 %	0.90 %	ISO 62
Particle Size	<= 80 Âμm	<= 80 Âμm	> 99 wt.%; DIN EN ISO 4610

Mechanical Properties	Metric	English	Comments
Hardness, Shore D	80	80	ISO 868

Thermal Properties	Metric	English	Comments
Melting Point	202 °C	396 °F	ISO 11357-3
Vicat Softening Point	186 °C	367 °F	ISO 306
Flammability, UL94	V-2	V-2	ISO1210
	@Thickness 1.60 mm	@Thickness 0.0630 in	
	V-2	V-2	IS01210
	@Thickness 3.20 mm	@Thickness 0.126 in	

Electrical Properties	Metric	English	Comments
Volume Resistivity	1.00e+14 ohm-cm	1.00e+14 ohm-cm	ISO 60093
Surface Resistance	1.00e+14 ohm	1.00e+14 ohm	ISO 60093

Descriptive Properties	Value	Comments
Salt Spray Resistance	< 1mm corrosion	ISO 7253; Testing according to WIS 4-52-01; 2000 hours



Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China