

## Sylvin Technologies 8940-80 Natural PVC Extrusion Compound

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Extruded

**Material Notes:**

Information provided by Sylvin Technologies Inc.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Sylvin-Technologies-8940-80-Natural-PVC-Extrusion-Compound.php](http://www.lookpolymers.com/polymer_Sylvin-Technologies-8940-80-Natural-PVC-Extrusion-Compound.php)

| Physical Properties | Metric    | English   | Comments |
|---------------------|-----------|-----------|----------|
| Specific Gravity    | 1.37 g/cc | 1.37 g/cc |          |

| Mechanical Properties      | Metric   | English  | Comments   |
|----------------------------|----------|----------|------------|
| Hardness, Shore A          | 80       | 80       | 10 seconds |
| Tensile Strength, Ultimate | 15.5 MPa | 2250 psi |            |
| Elongation at Break        | 370 %    | 370 %    |            |
| Tear Strength Test         | 360      | 360      |            |

| Processing Properties | Metric        | English       | Comments |
|-----------------------|---------------|---------------|----------|
| Melt Temperature      | 166 - 177 Â°C | 330 - 350 Â°F |          |

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China