

Sylvin Technologies 9604-90 LMW Clear PVC for Injection Molding

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Molded

Material Notes:

Information provided by Sylvin Technologies Inc.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Sylvin-Technologies-9604-90-LMW-Clear-PVC-for-Injection-Molding.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.25 g/cc	1.25 g/cc	
Thickness	1000 microns	39.4 mil	

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	90	90	10 seconds
Tensile Strength, Ultimate	13.1 MPa	1900 psi	
Elongation at Break	175 %	175 %	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	50.0 Å°C	122 Å°F	RTI
Flammability, UL94	HB	HB	

Optical Properties	Metric	English	Comments
Transmission, Visible	90 %	90 %	clear; thickness not quantified

Processing Properties	Metric	English	Comments
Melt Temperature	171 - 182 Å°C	340 - 360 Å°F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China