

Sylvin Technologies 9950-60 Natural PVC Molding Compound

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Molded

Material Notes:

Information provided by Sylvin Technologies Inc.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Sylvin-Technologies-9950-60-Natural-PVC-Molding-Compound.php

| Physical Properties | Metric | English | Comments |
|---------------------|-----------|-----------|----------|
| Specific Gravity | 1.31 g/cc | 1.31 g/cc | |

| Mechanical Properties | Metric | English | Comments |
|----------------------------|----------|----------|------------|
| Hardness, Shore A | 60 | 60 | 10 seconds |
| Tensile Strength, Ultimate | 8.27 MPa | 1200 psi | |
| Elongation at Break | 450 % | 450 % | |
| Tear Strength Test | 175 | 175 | |

| Processing Properties | Metric | English | Comments |
|-----------------------|---------------|---------------|----------|
| Melt Temperature | 154 - 166 Â°C | 310 - 330 Â°F | |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China