

TSE Industries Millathane® HT High Temperature-Resistant Millable Polyester Polyurethane, Hardness 93A

Category : Polymer , Thermoset , Polyester, TS , Polyurethane, TS , Thermoset Polyurethane, Elastomer, Unreinforced , Rubber or Thermoset Elastomer (TSE)

Material Notes:

MILLATHANE HT is a polyester millable polyurethane which has the ability to withstand elevated temperatures. Polyurethanes have been known for their excellent resistance to abrasion, impact, tear strength, oil and fuel resistance, and ozone resistance. The life expectancy of urethane is often 5 times longer than other elastomers, thus saving material costs and downtime expense. One shortcoming of polyurethanes is loss of physical properties at temperatures over 180°F (82°C). MILLATHANE HT has overcome this weakness. Non-Black with Peroxide Cure System Formulation Millathane HT100.0Hi-Sil 243 LD60.0Di-Cup 40C1.0 All information provided by TSE Industries

Order this product through the following link:

http://www.lookpolymers.com/polymer_TSE-Industries-Millathane-HT-High-Temperature-Resistant-Millable-Polyester-Polyurethane-Hardness-93A.php

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	93	93	
Tensile Strength, Yield	19.73 MPa	2861 psi	
Elongation at Yield	343 %	343 %	
100% Modulus	0.007288 GPa	1.057 ksi	
200% Modulus	0.01298 GPa	1.882 ksi	
300% Modulus	0.01708 GPa	2.477 ksi	
Tear Strength	62.1 kN/m	354 pli	Die C

Processing Properties	Metric	English	Comments
Cure Time	10.0 min	0.167 hour	
	@Temperature 160 °C	@Temperature 320 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China