

TSE Industries Millathane® HT High Temperature-Resistant Millable Polyester Polyurethane with Sundex 790 Plasticizer

Category: Polymer, Thermoset, Polyester, TS, Polyurethane, TS, Thermoset Polyurethane, Elastomer, Unreinforced, Rubber or Thermoset Elastomer (TSE)

Material Notes:

MILLATHANE HT is a polyester millable polyurethane which has the ability to withstand elevated temperatures. Polyurethanes have been known for their excellent resistance to abrasion, impact, tear strength, oil and fuel resistance, and ozone resistance. The life expectancy of urethane is often 5 times longer than other elastomers, thus saving material costs and downtime expense. One shortcoming of polyurethanes is loss of physical properties at temperatures over 180°F (82°C). MILLATHANE HT has overcome this weakness.FormulationMillathane HT100.0Zinc Stearate0.5MBTS4.0MBT2.0THANECURE® ZM1.0Sulfur1.5N-330 Black20.0Sundex 79015.0All information provided by TSE Industries

Order this product through the following link:

http://www.lookpolymers.com/polymer_TSE-Industries-Millathane-HT-High-Temperature-Resistant-Millable-Polyester-Polyurethane-with-Sundex-790-Plasticizer.php

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	60	60	
Tensile Strength, Yield	30.36 MPa	4404 psi	
Elongation at Yield	540 %	540 %	
100% Modulus	0.00203 GPa	0.295 ksi	
200% Modulus	0.00501 GPa	0.727 ksi	
300% Modulus	0.009818 GPa	1.424 ksi	
Tear Strength	45.7 kN/m	261 pli	Die C

Thermal Properties	Metric	English	Comments	
Brittleness Temperature	-53.0 °C	-63.4 °F		

Processing Properties	Metric	English	Comments
Cure Time	20.0 min	0.333 hour	
	@Temperature 154 °C	@Temperature 310 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842



Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China