

Techmer ES Plaslube® J-1/AF/15/TF/10 NAT PA66

Category : Polymer , Thermoplastic , Nylon , Nylon 66 , Nylon 66, Aramid Fiber Filled

Material Notes:

Order this product through the following link:

http://www.lookpolymers.com/polymer_Techmer-ES-Plaslube-J-1AF15TF10-NAT-PA66.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.27 g/cc	1.27 g/cc	ASTM D792
Water Absorption	0.75 %	0.75 %	24 Hrs; ASTM D570
Linear Mold Shrinkage	0.010 - 0.015 cm/cm	0.010 - 0.015 in/in	ASTM D955

Mechanical Properties	Metric	English	Comments
Hardness, Rockwell R	100 - 110	100 - 110	ASTM D785
Tensile Strength at Break	75.8 MPa	11000 psi	ASTM D638
Elongation at Break	5.0 %	5.0 %	ASTM D638
Flexural Strength	124 MPa	18000 psi	ASTM D790
Flexural Modulus	3.52 GPa	510 ksi	ASTM D790
Izod Impact, Notched	0.454 J/cm	0.850 ft-lb/in	ASTM D256

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China