

Techmer ES Plaslube® J-3/30/TF/13/SI/2 Nylon 6, 30% GFR, 13% PTFE, 2% Silicone

Category : Polymer , Thermoplastic , Nylon , Nylon 6 , Nylon 6, Glass Fiber/Solid Lube Filled

Material Notes:

Plaslube glass fiber reinforced polytetrafluoroethylene (PTFE) lubricated nylon 612 grades offer a unique balance of excellent wear and friction performance with good dimensional stability and mechanical strength. These characteristics are typical of gear train, pulley, and other bearing applications. Further wear and friction performance can be achieved by utilizing both PTFE and silicone. For less dimensionally critical applications, our nylon 6 grades offer similar performance characteristics.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Techmer-ES-Plaslube-J-330TF13SI2-Nylon-6-30-GFR-13-PTFE-2-Silicone.php

Physical Properties	Metric	English	Comments
Density	1.48 g/cc	0.0535 lb/in ³	ASTM D792
Water Absorption	0.75 %	0.75 %	24 hrs. ASTM D570
Linear Mold Shrinkage	0.0030 cm/cm @Thickness 3.17 mm	0.0030 in/in @Thickness 0.125 in	ASTM D955

Mechanical Properties	Metric	English	Comments
Tensile Strength, Ultimate	165 MPa	24000 psi	ASTM D638
Flexural Yield Strength	228 MPa	33000 psi	ASTM D790
Flexural Modulus	9.31 GPa	1350 ksi	ASTM D790
Izod Impact, Notched	1.39 J/cm @Thickness 3.17 mm	2.60 ft-lb/in @Thickness 0.125 in	ASTM D256
Coefficient of Friction, Dynamic	0.20	0.20	
Coefficient of Friction, Static	0.17	0.17	
K (wear) Factor	121 x 10 ⁻⁸ mm ³ /N-M	60.0 x 10 ⁻¹⁰ in ³ - min/ft-lb-hr	Thrust washer at 2000 PV
Limiting Pressure Velocity	0.560 MPa-m/sec	16000 psi-ft/min	at 100 FPM, ambient temperature, thrust washer.

Thermal Properties	Metric	English	Comments
Deflection Temperature at 1.8 MPa (264 psi)	213 °C	415 °F	ASTM D648

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China