

Techmer ES Plaslube® NY-1/TF/12 Nylon 66, 12% PTFE

Category : Polymer , Thermoplastic , Nylon , Nylon 66 , Nylon 66, PTFE Filled

Material Notes:

Plaslube polytetrafluoroethylene (PTFE) lubricated nylon 66 grades offer the best wear and friction properties of any unreinforced, lubricated nylon compounds, making them ideal materials for bearings and bushings.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Techmer-ES-Plaslube-NY-1TF12-Nylon-66-12-PTFE.php

Physical Properties	Metric	English	Comments
Density	1.20 g/cc	0.0434 lb/in ³	ASTM D792
Water Absorption	0.70 %	0.70 %	24 hrs. ASTM D570

Mechanical Properties	Metric	English	Comments
Tensile Strength, Ultimate	68.9 MPa	10000 psi	ASTM D638
Elongation at Break	4.5 %	4.5 %	ASTM D638
Flexural Yield Strength	98.6 MPa	14300 psi	ASTM D790
Flexural Modulus	2.90 GPa	420 ksi	ASTM D790
Izod Impact, Notched	0.427 J/cm @Thickness 3.17 mm	0.800 ft-lb/in @Thickness 0.125 in	ASTM D256

Thermal Properties	Metric	English	Comments
Deflection Temperature at 1.8 MPa (264 psi)	93.3 Å°C	200 Å°F	ASTM D648

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China