

## Technetics Group PLASTOLON™ PTFE Filtration Sewing Thread (Unverified Data\*\*)

Category : Polymer , Thermoplastic , Fluoropolymer , PTFE

**Material Notes:**

Information provided by Technetics Group (formerly Plastomer Technologies)

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Technetics-Group-PLASTOLON-PTFE-Filtration-Sewing-Thread-nbspUnverified-Data.php](http://www.lookpolymers.com/polymer_Technetics-Group-PLASTOLON-PTFE-Filtration-Sewing-Thread-nbspUnverified-Data.php)

Physical Properties	Metric	English	Comments
Fiber Count	667 - 2670 dtex	600 - 2400 denier	

Mechanical Properties	Metric	English	Comments
Elongation at Break	>= 5.0 %	>= 5.0 %	
Tenacity	0.265 N/tex	3.00 g/denier	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	288 °C	550 °F	
Minimum Service Temperature, Air	-184 °C	-300 °F	

Descriptive Properties	Value	Comments
Chemical Inertness	Excellent	
Ply	Single or multiple	
Twist	S or Z	

### Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China