

Teknor Apex APEXÂ® 3060-H Polyvinyl Chloride, Flexible

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Flexible Grade

Material Notes:

Material Status-Commercial: ActiveAvailability-North AmericaTest Standards Available-ASTMFeatures-Good FlexibilityUses-General Purpose, ProfilesAppearance-Natural Color, OpaqueForms-PelletsProcessing Method-ExtrusionInformation provided by Teknor Apex Company

Order this product through the following link:

http://www.lookpolymers.com/polymer_Teknor-Apex-APEX-3060-H-Polyvinyl-Chloride-Flexible.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.35 g/cc	1.35 g/cc	23Â°C; ASTM D792

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	60	60	15 seconds; ASTM D2240
	66	66	ASTM D2240
Tensile Strength at Break	8.96 MPa	1300 psi	ASTM D412
Tensile Strength, Yield	2.90 MPa	420 psi	100%; ASTM D412
Elongation at Break	420 %	420 %	ASTM D412
Tear Strength	26.3 kN/m	150 pli	Die C; ASTM D624

Thermal Properties	Metric	English	Comments
Brittleness Temperature	-42.0 Â°C	-43.6 Â°F	ASTM D746

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China