

Teknor Apex APEX® 3202-65 Polyvinyl Chloride, Flexible

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Flexible Grade

Material Notes:

Material Status-Commercial: ActiveAvailability-North AmericaTest Standards Available-ASTMUses-Caps, Closure, Connectors, Food Service Applications, Safety Equipment, Valves/Valve Parts Appearance-ClearForms-PelletsProcessing Method-Injection MoldingInformation provided by Teknor Apex Company

Order this product through the following link:

http://www.lookpolymers.com/polymer_Teknor-Apex-APEX-3202-65-Polyvinyl-Chloride-Flexible.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.21 g/cc	1.21 g/cc	23°C; ASTM D792

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	65	65	15 seconds; ASTM D2240
Tensile Strength, Yield	14.5 MPa	2100 psi	ASTM D412
Elongation at Break	400 %	400 %	ASTM D412

Thermal Properties	Metric	English	Comments
Brittleness Temperature	-39.0 °C	-38.2 °F	ASTM D746

Processing Properties	Metric	English	Comments
Melt Temperature	171 °C	340 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China