

## Teknor Apex APEX<sup>®</sup> 3211-65 Polyvinyl Chloride, Flexible

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Flexible Grade , PVC, Wire and Cable Grade

### Material Notes:

Material Status-Commercial: ActiveAvailability-North AmericaTest Standards Available-ASTMUses-Automotive Applications, Non-specific Food Applications, General Purpose, Medical Applications, Modeling Material, Toys, Wire & Cable ApplicationsAppearance-Natural Color, OpaqueForms-PelletsProcessing Method-Injection MoldingInformation provided by Teknor Apex Company

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Teknor-Apex-APEX-3211-65-Polyvinyl-Chloride-Flexible.php](http://www.lookpolymers.com/polymer_Teknor-Apex-APEX-3211-65-Polyvinyl-Chloride-Flexible.php)

Physical Properties	Metric	English	Comments
Specific Gravity	1.34 g/cc	1.34 g/cc	23°C; ASTM D792

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	65	65	15 seconds; ASTM D2240
Tensile Strength, Yield	4.62 MPa	670 psi	100%; ASTM D412
	11.0 MPa	1600 psi	ASTM D412
Elongation at Break	380 %	380 %	ASTM D412

Thermal Properties	Metric	English	Comments
Brittleness Temperature	-37.8 °C	-36.0 °F	ASTM D746

Processing Properties	Metric	English	Comments
Melt Temperature	171 °C	340 °F	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China