

## Teknor Apex APEX<sup>®</sup> 3302-90 Polyvinyl Chloride, Flexible

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Flexible Grade

**Material Notes:**

Material Status-Commercial: ActiveAvailability-North AmericaTest Standards Available-ASTM Uses- Medical Applications, Tubing, Appearance-ClearForms-PelletsProcessing-ExtrusionInformation provided by Teknor Apex Company

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Teknor-Apex-APEX-3302-90-Polyvinyl-Chloride-Flexible.php](http://www.lookpolymers.com/polymer_Teknor-Apex-APEX-3302-90-Polyvinyl-Chloride-Flexible.php)

Physical Properties	Metric	English	Comments
Specific Gravity	1.27 g/cc	1.27 g/cc	23°C; ASTM D792

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	90	90	15 seconds; ASTM D2240
Tensile Strength, Yield	14.5 MPa	2100 psi	100%; ASTM D412
	23.4 MPa	3400 psi	ASTM D412
Elongation at Break	340 %	340 %	ASTM D412

Thermal Properties	Metric	English	Comments
Brittleness Temperature	-12.0 °C	10.4 °F	ASTM D746

Processing Properties	Metric	English	Comments
Melt Temperature	191 °C	375 °F	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China