

Teknor Apex APEX[®] 3311-65 Polyvinyl Chloride, Flexible

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Flexible Grade , PVC, Wire and Cable Grade

Material Notes:

Material Status-Commercial: ActiveAvailability-North AmericaTest Standards Available-ASTM Uses-Automotive Applications, Food Service Applications, General Purpose, Medical Applications, Profiles, Toys, Tubing, Wire & Cable ApplicationsAppearance-Natural Color, OpaqueForms-PelletsProcessing-ExtrusionInformation provided by Teknor Apex Company

Order this product through the following link:

http://www.lookpolymers.com/polymer_Teknor-Apex-APEX-3311-65-Polyvinyl-Chloride-Flexible.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.34 g/cc	1.34 g/cc	23°C; ASTM D792

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	65	65	15 seconds; ASTM D2240
Tensile Strength, Yield	4.76 MPa	690 psi	100%; ASTM D412
	11.6 MPa	1680 psi	ASTM D412
Elongation at Break	390 %	390 %	ASTM D412

Thermal Properties	Metric	English	Comments
Brittleness Temperature	-41.0 °C	-41.8 °F	ASTM D746

Processing Properties	Metric	English	Comments
Melt Temperature	171 °C	340 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China