

Teknor Apex APEXÂ® 3703-75NT1 Polyvinyl Chloride, Flexible

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Flexible Grade

Material Notes:

Features: Non-Phthalate - TOTM Plasticizer Uses: Medical/Healthcare Applications Processing Method: Extrusion Forms:

Pellets Information Provided by Teknor Apex

Order this product through the following link:

http://www.lookpolymers.com/polymer_Teknor-Apex-APEX-3703-75NT1-Polyvinyl-Chloride-Flexible.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.20 g/cc	1.20 g/cc	ASTM D792

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	75	75	10 seconds; ASTM D2240
Tensile Strength at Break	16.5 MPa	2400 psi	ASTM D638
Elongation at Break	410 %	410 %	ASTM D638

Descriptive Properties	Value	Comments
Appearance	Clear	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China