

Teknor Apex APEXÂ® 80328-Y Polyvinyl Chloride, Flexible

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Flexible Grade , PVC, Wire and Cable Grade

Material Notes:

Notes: 75Â°C Insulation; RoHS Compliant Features: Sunlight Resistant (720 hours) Uses: Cable Jacketing; Insulation Agency Ratings: UL QMTT2 . E73402 Forms: Pellets Wire Types: TW Information Provided by Teknor Apex

Order this product through the following link:

http://www.lookpolymers.com/polymer_Teknor-Apex-APEX-80328-Y-Polyvinyl-Chloride-Flexible.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.43 g/cc	1.43 g/cc	ASTM D792

Mechanical Properties	Metric	English	Comments
Hardness, Shore C	85	85	10 seconds; ASTM D2240
Tensile Strength at Break	16.5 MPa	2400 psi	ASTM D638
Elongation at Break	320 %	320 %	ASTM D638

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	75.0 Â°C	167 Â°F	Continuous Use; ASTM D794
Brittleness Temperature	-29.0 Â°C	-20.2 Â°F	ASTM D746
Oxygen Index	23 %	23 %	ASTM D2863

Electrical Properties	Metric	English	Comments
Dielectric Constant	3.58	3.58	ASTM D150
	@Frequency 1.00e+6 Hz	@Frequency 1.00e+6 Hz	
	5.19	5.19	ASTM D150
	@Frequency 1000 Hz	@Frequency 1000 Hz	

Descriptive Properties	Value	Comments
Appearance	Opaque	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China