

Teknor Apex APEX[®] 80862-F Polyvinyl Chloride, Flexible

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Flexible Grade , PVC, Wire and Cable Grade

Material Notes:

Notes: 105[°]C Insulation; RoHS Compliant Uses: Wire and Cable Applications Forms: Pellets Information Provided by Teknor Apex

Order this product through the following link:

http://www.lookpolymers.com/polymer_Teknor-Apex-APEX-80862-F-Polyvinyl-Chloride-Flexible.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.30 g/cc	1.30 g/cc	ASTM D792

Mechanical Properties	Metric	English	Comments
Hardness, Shore C	90	90	10 seconds; ASTM D2240
Tensile Strength at Break	24.1 MPa	3500 psi	ASTM D638
Elongation at Break	240 %	240 %	ASTM D638

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	105 [°] C	221 [°] F	Continuous Use; ASTM D794
Brittleness Temperature	-30.0 [°] C	-22.0 [°] F	ASTM D746
Oxygen Index	30 %	30 %	ASTM D2863

Descriptive Properties	Value	Comments
Appearance	Opaque	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China