

Teknor Apex APEXÂ® 84853-L Polyvinyl Chloride, Flexible

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Flexible Grade

Material Notes:

Notes: 105Â°C Insulation; RoHS Compliant Features: Flame Retardant; High Heat Resistant Uses: Insulation Agency Ratings: UL 62 Forms: Pellets Wire Types: SJT; ST; SVT Information Provided by Teknor Apex

Order this product through the following link:

http://www.lookpolymers.com/polymer_Teknor-Apex-APEX-84853-L-Polyvinyl-Chloride-Flexible.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.38 g/cc	1.38 g/cc	ASTM D792

Mechanical Properties	Metric	English	Comments
Hardness, Shore C	75	75	10 seconds; ASTM D2240
Tensile Strength at Break	19.3 MPa	2800 psi	ASTM D638
Elongation at Break	290 %	290 %	ASTM D638

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	105 Â°C	221 Â°F	Continuous Use; ASTM D794
Brittleness Temperature	-17.0 Â°C	1.40 Â°F	ASTM D746
Oxygen Index	28 %	28 %	ASTM D2863

Descriptive Properties	Value	Comments
Appearance	Opaque	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China