

Teknor Apex APEXÂ® 89-P129A-NT Polyvinyl Chloride, Flexible

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Flexible Grade

Material Notes:

Notes: RoHS Compliant Features: High Heat Resistant; Low to no Migration; Oil Resistant Uses: Flexible Cord Jacketing Agency Ratings: UL 62 Forms: Pellets Information Provided by Teknor Apex

Order this product through the following link:

http://www.lookpolymers.com/polymer_Teknor-Apex-APEX-89-P129A-NT-Polyvinyl-Chloride-Flexible.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.25 g/cc	1.25 g/cc	ASTM D792

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	80	80	10 seconds; ASTM D2240
Tensile Strength at Break	19.2 MPa	2780 psi	ASTM D638
Elongation at Break	390 %	390 %	ASTM D638

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	105 Â°C	221 Â°F	Continuous Use; ASTM D794
Brittleness Temperature	-25.0 Â°C	-13.0 Â°F	ASTM D746
Oxygen Index	22 %	22 %	ASTM D2863

Descriptive Properties	Value	Comments
Appearance	Clear/Transparent	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China