

Teknor Apex APEXÂ® 90-A472R-100-NT Polyvinyl Chloride, Flexible

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Flexible Grade

Material Notes:

Material Status-Commercial: ActiveAvailability-North AmericaTest Standards Available-ASTMUses-Medical Applications, Caps, Closures, Valves/Valve Parts Appearance-ClearForms-PelletsProcessing Method-Injection MoldingInformation provided by Teknor Apex Company

Order this product through the following link:

http://www.lookpolymers.com/polymer_Teknor-Apex-APEX-90-A472R-100-NT-Polyvinyl-Chloride-Flexible.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.28 g/cc	1.28 g/cc	23Â°C; ASTM D792

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	75	75	15 seconds; ASTM D2240
Tensile Strength, Yield	20.0 MPa	2900 psi	ASTM D412
Elongation at Break	220 %	220 %	ASTM D412

Processing Properties	Metric	English	Comments
Melt Temperature	191 Â°C	375 Â°F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China