

Teknor Apex APEX[®] 94-A0098A-80 Polyvinyl Chloride, Flexible

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Flexible Grade

Material Notes:

Material Status-Commercial: ActiveAvailability-North AmericaTest Standards Available-ASTMFeatures-General Purpose Uses-General PurposeAppearance-Natural Color, OpaqueForms-PelletsProcessing Method-Injection Molding Information provided by Teknor Apex Company

Order this product through the following link:

http://www.lookpolymers.com/polymer_Teknor-Apex-APEX-94-A0098A-80-Polyvinyl-Chloride-Flexible.php

| Physical Properties | Metric | English | Comments |
|---------------------|-----------|-----------|------------------|
| Specific Gravity | 1.30 g/cc | 1.30 g/cc | 23Â°C; ASTM D792 |

| Mechanical Properties | Metric | English | Comments |
|-------------------------|----------|----------|------------------------|
| Hardness, Shore A | 80 | 80 | 15 seconds; ASTM D2240 |
| Tensile Strength, Yield | 16.2 MPa | 2350 psi | ASTM D412 |
| Elongation at Break | 350 % | 350 % | ASTM D412 |

| Thermal Properties | Metric | English | Comments |
|-------------------------|-----------|-----------|-----------|
| Brittleness Temperature | -28.0 Â°C | -18.4 Â°F | ASTM D746 |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China